

## Radial Pneus 2

The RP 2 presses allow to retread passenger car, light truck, 4x4 and aircraft tyres, can be manufactured tubeless, bladder and curing tube and with high belt to increase the tyre width range.

Heating by steam or electricity



### Technical features\*

	RP2H	RP2HH	RP2 HH AVIO
Ø DIAMETER OF THE CAVITY mm	830	880	880
HEIGHT OF THE CAVITY mm	230/280	280/330	320/380
MAX TYRE O.D. mm	800	850	850
MAX TYRE C.S. mm	260	310	360
WEIGHT Kg	1950	2080	2150
AIR CONSUMPTION Nlt/h	1450	1500	1550
STEAM CONSUMPTION Kg/h	16	18	18
MAX INFLAT. PRESSURE Bar**	16	16	23
ENGINE POWER HP	2	2	2
WIDTH mm	1750	1850	1850
LENGTH mm	1950	1980	1980
CLOSED HEIGHT mm	1200	1250	1320
OPEN HEIGHT mm	2100	2200	2300
TYRES SIZES	From 195/80R 15 to 265/60R 18	From 195/80R 15 to 325/50R 20	

\*\*standard configuration. Higher pressures on request

\*Dimensions and specification shown are not binding and could be changed without notice by the manufacturer