

## Radial Pneus 9 - 9H and 10

The RP 9 an 10 presses allow to retread tyres for agricultural purpose, aircraft and OTR.

The presses can be manufactured tubeless and with curing tube.



### Technical features\*

	RP 9	RP 9 H	RP 10
Ø DIAMETER OF THE CAVITY mm	2150	2150	880
HEIGHT OF THE CAVITY mm	750/850	800/1000	320/380
MAX TYRE O.D. mm	2080	2080	850
MAX TYRE C.S. mm	820	970	360
WEIGHT Kg	25000	29000	2150
AIR CONSUMPTION Nlt/h	7500	8000	1550
STEAM CONSUMPTION Kg/h	150	180	18
MAX INFLAT. PRESSURE Bar**	18	18	23
ENGINE POWER HP	10	10	2
WIDTH mm	3500	3500	1850
LENGTH mm	4700	4700	1980
CLOSED HEIGHT mm	2500	2650	1320
OPEN HEIGHT mm	5000	5150	2300
TYRES SIZES	From 23.5 R 25 to 29.5 R 29	From 23.5 R 25 to 35/60 R 33	From 24.00 R 35 to 37/25 R 35

\*\*standard configuration. Higher pressures on request

\*Dimensions and specification shown are not binding and could be changed without notice by the manufacturer