

MITICA OTR CNC Buffing Peeling machine



Buffing and peeling operations are fully controlled by PLC / CNC.

Tyres profile data storage

One or two manual arms depending on size.

Inclined frame to ease tyre loading/unloading.

Exhaust system available on request

Technical features*

| | 2500 up to 35" rim | 3300 up to 51" rim | 4100 up to 63" rim |
|--------------------------------|------------------------------|------------------------------|------------------------------|
| Machine width (mm) | 4500 | 5800 | 7700 |
| Machine length (mm) | 5600 | 6900 | 7400 |
| Machine height (mm) | 3400 | 4400 | 5150 |
| Weight (Kgs) | 11000 | 19000 | 28000 |
| Max Tyre dim (mm) | 2500 | 3300 | 4100 |
| Min Tyre dim (mm) | 1200 | 1400 | 1400 |
| Max Tyre width (mm) | 1000 | 1250 | 1550 |
| Max inflation pressure (bar) | 1,5 | 1,5 | 1,5 |
| Max air working pressure (bar) | 8 | 8 | 8 |
| Total installed power (Kw) | 78 | 78 | 78 |
| Voltage | 400 V 50 Hz | 400 V 50 Hz | 400 V 50 Hz |

Detail of CNC buffing/peeling head

